

TWIST

TERMOALDANTI

TERMOALDANTI HB






PELABILI

PELABILI HB






FILM PER CONVERTER

LAMINATI BASE PP e HB

Twist

	Cecronil® PET-NFC	18-22-27 microns
	Cecronil® PET-NFC WHITE	18-22 microns
	Cecronil® PET-NFC METALLISED	18-22-27 microns
	Cecronil® PET-NFCV WHITE CAVITATED	24-31 microns
	Cecronil® PET-NFCV WHITE CAVITATED METALLISED	24-31 microns

Termosaldanti

	Cecronil® PET-HSC	15-20-25-30-35 microns
	Cecronil® PET-HSC ANTIFOG	15-20-25-30 microns
	Cecronil® PET-HSC WHITE OPAQUE	20-25-30 microns
	Cecronil® PET-HSC METALLISED	20-25-30 microns
	Cecronil® PET-HSC WHITE OPAQUE METALLISED	20-25 microns



Termosaldanti alta barriera

	Cecronil® COVIOLOCK ALOX	15-20-25-30 microns
	Cecronil® COVIOLOCK ALOX C	15-20-25-30 microns
	Cecronil® COVIOLOCK ALOX C+	15-20-25-30 microns

Pelabili

	Cecronil® COVIPEEL	12-18-23-30-36 microns
--	---------------------------	------------------------





Pelabili alta barriera

	Cecronil® COVIPEEL ALOX C	12-18-23-30-36 microns
	Cecronil® COVIPEEL ALOX C+	12-18-23-30-36 microns

Film per converter

	Cecronil® COVIALOX	12-18-23-30-36 microns
	Cecronil® COVIALOX C	12-18-23 30-36 microns
	Cecronil® COVIALOX C+	12-18-23-30-36 microns

Laminati base PP e HB

	Cecronil® COVIOLOCK-PP	52-62 microns
	Cecronil® COVIOLOCK ALOX-PP	52-62 microns
	Cecronil® COVIOLOCK ALOX-PP C+	52-68 microns
	Cecronil® COVIPEEL-PP	52-62 microns
	Cecronil® COVIPEEL ALOX-PP	52-62-73 microns